

INTRODUCING  
THE ALL NEW 2018 EDITION

# *Pulsar* THE BLACK PACK

THE BLACK BEASTS HAVE ARRIVED. WITH MENACING LOOKS AND LETHAL POWER,  
THE PULSAR 220F, 180 AND 150 ARE HERE TO RULE THE STREETS.  
GEAR UP TO GO BEAST MODE AND RIDE FEARLESSLY.





# pulsar

DEFINITELY MALE



## TECHNICAL SPECS

### ENGINE

Type  
Displacement (cc)  
Max power (PS @ RPM)  
Max torque (NM @ RPM)

### SUSPENSION

Front  
Rear

### BRAKES

Front  
Rear

### TYRES

Front  
Rear

### FUEL TANK

Total litres

### ELECTRICALS

System  
Headlamp

### DIMENSIONS

Length (mm)  
Width (mm)  
Height (mm)  
Ground clearance (mm)  
Wheelbase (mm)  
Kerb weight (kg)

## PULSAR 220F

4-stroke, 2-Valve, Twin Spark BSIV Compliant, DTS-i Engine, Oil cooled  
220 cc  
20.93 @ 8500  
18.55 @ 7000

Telescopic, with anti-friction bush  
5 way adjustable, Nitrox shock absorber

260 mm Disc  
230 mm Disc

90/90 - 17" - Tubeless  
120/80 - 17" - Tubeless

15 L

12 V Full DC  
Low - Projector lamp 55w,  
High - Ellipsoidal lamp 55w,  
With AHO (Auto Headlamp On)

2035  
750  
1115  
165  
1350  
155

## PULSAR 180

4-stroke, 2-Valve, Twin Spark BSIV Compliant, DTS-i Engine, Air cooled  
178.6 cc  
17.02 @ 8500  
14.22 @ 6500

Telescopic with Anti-friction bush  
5 way adjustable, Nitrox shock absorber

260 mm Disc  
230 mm Disc

90/90 - 17" - Tubeless  
120/80 - 17" - Tubeless

15 L

12 V Full DC  
35/35 W with 2 pilot lamps,  
With AHO (Auto Headlamp On)

2035  
765  
1115  
165  
1345  
145

## PULSAR 150

4-Stroke, 2-Valve,  
Twin Spark BSIV Compliant DTS-i Engine  
149 cc  
14 @ 8000  
13.4 @ 6000

Telescopic, with anti-friction bush  
5 way adjustable, Nitrox shock absorber

240 mm Disc  
130 mm Drum

80/100 - 17" - Tubeless  
100 / 90 - 17" - Tubeless

15 L

12 V Full DC  
35/35 W with 2 pilot lamps,  
With AHO (Auto Headlamp On)

2055  
755  
1060  
165  
1320  
144

### Also available in



### Chrome Black



### Dyno Red



### Nuclear Blue



## TECHNICAL SPECS

### PULSAR 220F

### PULSAR 180

### PULSAR 150

#### ENGINE

Type  
Displacement (cc)  
Max power (PS @ RPM)  
Max torque (NM @ RPM)

4-stroke, 2-Valve,  
Twin Spark BSIV Compliant,  
DTS-i Engine, Oil cooled  
220 cc  
20.93 @ 8500  
18.55 @ 7000

4-stroke, 2-Valve,  
Twin Spark BSIV Compliant,  
DTS-i Engine, Air cooled  
178.6 cc  
17.02 @ 8500  
14.22 @ 6500

4-Stroke, 2-Valve,  
Twin Spark BSIV Compliant  
DTS-i Engine  
149 cc  
14 @ 8000  
13.4 @ 6000

#### SUSPENSION

Front  
Rear

Telescopic, with anti-friction bush  
5 way adjustable,  
Nitrox shock absorber

Telescopic with Anti-friction bush  
5 way adjustable,  
Nitrox shock absorber

Telescopic, with anti-friction bush  
5 way adjustable,  
Nitrox shock absorber

#### BRAKES

Front  
Rear

260 mm Disc  
230 mm Disc

260 mm Disc  
230 mm Disc

240 mm Disc  
130 mm Drum

#### TYRES

Front  
Rear

90/90 - 17" - Tubeless  
120/80 - 17" - Tubeless

90/90 - 17" - Tubeless  
120/80 - 17" - Tubeless

80/100 - 17" - Tubeless  
100/90 - 17" - Tubeless

#### FUEL TANK

Total litres

15 L

15 L

15 L

#### ELECTRICALS

System  
Headlamp

12 V Full DC  
Low - Projector lamp 55w,  
High - Ellipsoidal lamp 55w,  
With AHO (Auto Headlamp On)

12 V Full DC  
35/35 W with 2 pilot lamps,  
With AHO (Auto Headlamp On)

12 V Full DC  
35/35 W with 2 pilot lamps,  
With AHO (Auto Headlamp On)

#### DIMENSIONS

Length (mm)  
Width (mm)  
Height (mm)  
Ground clearance (mm)  
Wheelbase (mm)  
Kerb weight (kg)

2035  
750  
1165  
165  
1350  
155

2035  
765  
1115  
165  
1345  
145

2055  
755  
1060  
165  
1320  
144

**pulsar**  
DEFINITELY MALE