







SPECIFICATIONS

Type Air Cooled, 4 - Stroke Single Cylinder Displacement 124.7 cc Maximum Power 8.6 kW @7500 Revolutions per minute(rpm) Maximum Torque 11 N-m@6000 Revolutions per minute(rpm) Bore x Stroke 52.4 x 57.9 mm Compression Ratio 10.01 Fuel System (FI)
Maximum Power 8.6 kW @7500 Revolutions per minute(rpm) Maximum Torque 11 N-m@6000 Revolutions per minute(rpm) Bore x Stroke 52.4 x 57.9 mm Compression Ratio 10.01
Maximum Torque 11 N-m@6000 Revolutions per minute(rpm) Bore x Stroke 52.4 x 57.9 mm Compression Ratio 10.01
Bore x Stroke 52.4 x 57.9 mm Compression Ratio 10.01
Compression Ratio 10,01
Fuel System (FI)
ruei system (ri)
Ignition System DC - Fully Transistorised Ignition (ECU)
Starting Self Start
TRANSMISSION
Clutch Wet Multiplate
Gear Box 4-Speed Constant Mesh
CHASSIS
Type Tubular Double Cradle Type
QUODENIAM
SUSPENSION
Front Telescopic Hydraulic Shock Absorbers
Rear 5-step adjustable hydraulic shock absorbers
DDAVEC
BRAKES
Front Disc 240 mm Dia, Pad - Non-asbestos Type
Rear Drum Internal Expanding Shoe Type - 130 mm
Liners - Non-asbestos Type

TYRE SIZE		
Tyre Size	Front Rear	80/100-18 47P 90/90-18 51P
ELECTRICALS		
Battery Head Lamp Tail / Stop Lamp Turn signal Lamp		12 V - 3 Ah (MF 4) 12 V - 35 W / 35 W - Halogen Bulb, (MFR) LED Type 12 V - 10Wx4 (Amber Bulb) With Clear Lens (MFR)
SERVICE DATA		
Engine Oil Grade Fuel Tank Capacity Reserve		SAE 10 W 30 SJ Grade 10 Litre 1.5 Litre
DIMENSIONS		
L x W x H Wheelbase Ground Clearance		2023 x 766 x 1091 mm 1262 mm 159 mm
WEIGHTS		
Kerb Weight		127 kg













