

HF Deluxe

FLEX FUEL

SPECIFICATIONS

ITEM	HF Deluxe Flex	
Engine	<p>Engine Type</p> <p>Maximum power</p> <p>Maximum torque</p> <p>Bore and stroke mm</p> <p>Displacement</p> <p>Fuel Compatibility</p>	<p>Air cooled, 4-stroke, Single cylinder, OHC</p> <p>6.3kW (with E85) @ 8000 rpm</p> <p>8.3 N-m (with E85) @ 6000 rpm</p> <p>50.0x49.5 mm</p> <p>97.2 cc</p> <p>E5 to E85 Fuel</p>
Transmission	<p>Frame type</p> <p>Transmission Type</p> <p>Clutch system</p> <p>Starting System</p>	<p>Tubular double cradle</p> <p>4 Speed Constant Mesh</p> <p>Multiplate wet type</p> <p>Electric start</p>
Suspension	<p>Front suspension</p> <p>Rear suspension</p>	<p>Telescopic hydraulic shock absorber</p> <p>Swingarm with 2 step hydraulic shock absorber</p>
Tyres	<p>Front tyre size</p> <p>Rear tyre size</p>	<p>80/100-18 M/C 47P</p> <p>80/100-18 M/C 54P</p>
Electrical System	<p>Battery capacity</p> <p>Headlamp</p> <p>Tail/ Stop lamp</p> <p>Turn signal lamp</p>	<p>MF Battery : 12 V, 3Ah</p> <p>12V 35/35W Halogen bulb</p> <p>12V 5/21W-MFR</p> <p>12V 10Wx4-MFR</p>
Dimensions	<p>Overall Length</p> <p>Overall Width</p> <p>Overall Height</p> <p>Wheelbase</p> <p>Saddle Height</p> <p>Ground Clearance</p> <p>Kerb weight</p>	<p>1965 mm</p> <p>720 mm</p> <p>1045 mm</p> <p>1235 mm</p> <p>805 mm</p> <p>165 mm</p> <p>112.5 kg</p>