

Splendor+

FLEX FUEL

SPECIFICATIONS

ITEM	Splendor+ Flex	
Engine	Engine Type Maximum power Maximum torque Bore and stroke mm Displacement Fuel Compatibility	Air cooled, 4-stroke, Single cylinder, OHC 6.3kW (with E85) @ 8000 rpm 8.3 N-m (with E85) @ 6000 rpm 50.0x49.5 mm 97.2 cc E5 to E85 Fuel
Transmission	Frame type Transmission Type Clutch system Starting System	Tubular double cradle 4 Speed Constant Mesh Multiplate Wet Type Electric Start
Suspension	Front suspension Rear suspension	Telescopic Hydraulic Shock absorber 5 Step adjustable Hydraulic Shock absorber
Tyres	Front tyre size Rear tyre size	80/100-18 M/C 47P 80/100-18 M/C 54P
Electrical System	Battery capacity Headlamp Tail/ Stop lamp Turn signal lamp USB Charger	MF Battery : 12 V, 3Ah 12V 35/35W Halogen bulb 12V 5/10W-MFR 12V 10Wx4-MFR 1A +/- 50mA (output current)
Dimensions	Overall Length Overall Width Overall Height Wheelbase Saddle Height Ground Clearance Kerb weight	2000 mm 720 mm 1052 mm 1236 mm 785 mm 165 mm 113 kg