



Badhta bharosa,
badhta yaarana meelon ka.

WITH **IBS**
INTEGRATED BRAKING SYSTEM

Combined Front-Rear Braking / Shorter Stopping Distance / Enhanced Stability



*Conditions apply

Accessories and features shown may not be a part of standard fitment.

SPECIFICATIONS



ENGINE

Type	Air cooled, 4 - Stroke Single Cylinder OHC
Displacement	97.2 cc
Maximum Power	6.15 kW (8.36 Ps) @ 8000 Revolutions per minute
Maximum Torque	0.82 Kg-m (8.05 N-m) @ 5000 Revolutions per minute
Compression Ratio	9.9:1
Starting	Self Start
Ignition	DC - Digital CDI

TRANSMISSION

Clutch	Multiplate Wet
Gear box	4 Speed Constant Mesh

CHASSIS

Type	Tubular Double Cradle Type
------	----------------------------

SUSPENSION

Front	Telescopic Hydraulic Shock Absorbers
Rear	Swing Arm with 5 Step Adjustable Hydraulic Shock Absorber

WHEELS AND TYRES

Tyre	Front	80/100-18 M/C 47P (Tubeless)
	Rear	80/100-18 M/C 54P (Tubeless)
Brakes	Front	Internal Expanding Shoe Type (130 mm) - Non Asbestos type
	Rear	Internal Expanding Shoe Type (130 mm) - Non Asbestos type

ELECTRICALS

Battery	12 V 2.5 Ah (Kick) / 12V-3 Ah MF (Self)
Head Lamp	12 V - 35 W / 35 W - Halogen Bulb (Multi-Reflector Type)
Tail Lamp	12 V - 5 / 10W (Multi-Reflector)

DIMENSIONS

Length	2000 mm
Width	720 mm
Height	1040 mm
Wheelbase	1230 mm
Ground clearance	159 mm

WEIGHTS

Kerb weight	109 kgs (Kick Start)/ 112.3 kgs (Electric Start)
Max.Payload	130 kgs

CAPACITY

Fuel Tank Capacity	10.5 Litre
Reserve	1 Litre (Usable Reserve)



Fuel Saving i3s Technology



Exciting Body Graphics



Stylish Alloy Wheels



APDV Engine
With Superb Mileage



Always Headlamp On(AHO)
for Added Safety

This product is BS-IV compliant.

AHO (Always Headlamp On) automatically switches the headlamp on when you start the engine.

- Available in standard variant as well.
- It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice.

Regd. Office: Hero MotoCorp Ltd., 34, Community Centre, Basant Lok, Vasant Vihar, New Delhi - 110057, India. CIN: L35911DL1984PLC017354. Phone No.: 011 - 46044100, Fax: 011 - 26143321, 26143198. Accessories and features shown may not be part of standard fitment. Always wear a helmet while riding a two wheeler. For further information, please contact the nearest Hero MotoCorp authorised outlet or call our toll free no.: 1800 - 266 - 0018 or visit our website www.heromotocorp.com.

