

## CHALLENGE THE EXTREME

THE FASTEST\*160CC



TREME 4
1507
2024 EDITION



EVERY NUT, EVERY BOLT.

EVERY LAP, EVERY RACE.

WE SET AN IMPOSSIBLE PACE.

NEVER PAUSING FOR ANYTHING.
NEVER COMPROMISING.


WE'RE THE ONES WHO PLAY IT FAST.
WE'RE THE ONES WHO OWN THE PLAY.

WE CHALLENGE THE EXTREME.













# IMPROVED SPEEDOMETER BRIGHTNESS



High Speed Meets High Visibility.

300% improvement in LCD brightness ensures improved readability even under direct sunlight.

## EXTREMELY LOADED

IMPROVED SPEEDOMETER BRIGHTNESS

DRAG TIMER

COMFORTABLE PILLION SEAT

NEW TAIL LIGHT

PANIC BRAKE ALERT

DUAL CHANNEL ABS



#### THE FASTEST 160CC



### **SPECIFICATIONS**

	SPECS	PRO VARIANT
ENGINE	Engine Type	4 Stroke, Air-Oil Cooled, 4 Valve
	Bore & Stroke	66.5 mm x 47.0 mm
	Displacement (cm³)	163.2
	Compression Ratio	10.1:1
	Max Power	16.9 Ps/12.4kW @ 8500rpm
	Max Torque	14.6 Nm @6500 rpm
	Transmission Type	5 Speed Constant Mesh
	Clutch Type	Multiplate Wet
CHASSIS	Frame Type	Tubular Underbone Diamond Type
	Swing Arm	Box type (50x30mm rectangle tube)
SUSPENSION	Front Suspension Type	KYB USD Forks, 37mm Dia
	Rear Suspension Type	7 Step Adjustable Monoshock
BRAKES	Front Brake type	Disc 276 mm (Petal)
	Rear Brake Type	Disc 220 mm (Petal)
WHEELS & TYRES	Wheel Type	Alloy
	Front Tyre Size	100/80 -17 (TL)
	Rear Tyre Size	130/70 R 17 (TL)
ELECTRICALS	Lamps	LED Headlight with Position Lamp, LED Tail lamp and LED Winkers
	Battery (V-Ah)	12 V-6AH (VRLA)
	Starting System	Self Start
WEIGHT & DIMENSIONS	Overall Length (mm)	2029
	Overall Width (mm)	793
	Overall Height (mm)	1052
	Wheelbase (mm)	1333
	Seat Height (mm)	795
	Ground Clearance (mm)	165
	Fuel Tank Capacity (L)	12
	Kerb Weight (kg)	146

