2024 KLX 140R F

Starting At Rs.4,11,000/- (Ex-Showroom)

GET ON-ROAD PRICE

TYRE - FRONT

TYRE - REAR

WHEELBASE

SEAT HEIGHT

GROUND CLEARANCE

(https://kawasaki-india.com/on-road-price-estimator/)

*Product pictures shown are for illustration purpose only.

*Actual product may vary from the picture shown here.

*Specification and pricing are subject to change.



AVAILABLE COLOURS



Lime Green

Engine & Transmission	
ТҮРЕ	4st, 1-cyl, SOHC, 2val, Air-cooled
DISPLACEMENT	144 cm3
BORE AND STROKE	58.0 x 54.4 mm
COMPRESSION RATIO	9.5
VALVE SYSTEM	-
FUEL SYSTEM	-
FUEL TYPE / MINIMUM OCTANE RATING	Carburetor: KEIHIN PB20
IGNITION	DC-CDI
STARTING	EL. Starter
LUBRICATION	Forced Lub. Wet
TRANSMISSION	5-speed, return
MAXIMUM POWER	8.3 kW {11PS} / 8,000 min-1
Maximum power with ram Air	-
MAXIMUM TORQUE	12 N-m {1.2 kg-m} / 6,000 min-1 (USA/CAN) 12.0 N-m {1.2 kgm} / 6,000 min-1 (EUR/IDN/THA)
ELECTRONIC RIDER AID	
Dimensions & Chassis	
FRAME TYPE	Tubular, semi-double cradle
RAKE / TRAIL	27.0 o /116 mm

2.75-21 45M

4.10-18 59M

1,330 mm

315 mm

860 mm

Dimensions & Chassis		
CURB MASS	99 kg	
FUEL CAPACITY	5.8	
OVERALL DIMENSIONS (L X W X H)	2,005 x 790 x 1,135 mm.	
Brakes & Suspension		
FRONT / WHEEL TRAVEL	Telescopic fork/ 190mm	
REAR / WHEEL TRAVEL	Uni Trak Swingarm/ 200 mm	
BRAKE - FRONT	Single disc / 192 mm	
CALIPER - FRONT	-	
BRAKE - REAR	Single disc /156 mm	
CALIPER - REAR	-	