

2025 Z650 BS6

Starting At Rs.6,79,000 /- (Ex-Showroom)

GET ON-ROAD PRICE

(<https://kawasaki-india.com/on-road-price-estimator/>)

\*Product pictures shown are for illustration purpose only.

\*Actual product may vary from the picture shown here.

\*Specification and pricing are subject to change.



AVAILABLE COLOURS

 Metallic Matte Dark Gray /  Metallic Spark Black

Engine & Transmission

TYPE	Liquid-cooled, 4-stroke, parallel twin
DISPLACEMENT	649 cm3
BORE AND STROKE	83.0 x 60.0 mm
COMPRESSION RATIO	10.8:1
VALVE SYSTEM	DOHC, 8 valves
FUEL SYSTEM	Fuel injection: ø36 mm x 2 with dual throttle valves
FUEL TYPE / MINIMUM OCTANE RATING	Unleaded petrol/RON91
IGNITION	Digital
STARTING	Electric
LUBRICATION	Forced lubrication, semi-dry sump
TRANSMISSION	6 Speed, Return
MAXIMUM POWER	50.2 kW {68 PS} / 8,000 rpm
MAXIMUM POWER WITH RAM AIR	-
MAXIMUM TORQUE	64.0 N.m {6.5 kgf.m} / 6,700 rpm
ELECTRONIC RIDER AID	

Dimensions & Chassis

FRAME TYPE	Trellis, high-tensile steel
RAKE / TRAIL	24.0° / 100 mm
TYRE - FRONT	120/70ZR17M/C (58W)
TYRE - REAR	160/60ZR17M/C (69W)

**Dimensions & Chassis**

WHEELBASE	1,410 mm
GROUND CLEARANCE	130 mm
SEAT HEIGHT	790 mm
CURB MASS	188 kg
FUEL CAPACITY	15 litres
OVERALL DIMENSIONS (L X W X H)	2,055 mm x 765 mm x 1,065 mm

**Brakes & Suspension**

FRONT / WHEEL TRAVEL	ø41 mm telescopic fork/125mm
REAR / WHEEL TRAVEL	Horizontal Back-link with adjustable preload/130mm
BRAKE - FRONT	Dual semi-floating ø300 mm petal discs
CALIPER - FRONT	Dual piston
BRAKE - REAR	Single ø220 mm petal disc
CALIPER - REAR	Single-piston