







CRAFTED FOR POWER

Liquid-Cooled-Oil-Coolant Technology

Provides efficient thermal management.
Keeps the high-revving engine cool in long race distances.

Volumetric Efficiency

tappet arrangement provides an 8% increase in volumetric efficiency.

Compact Engine Design

The horizontally split crank case keeps the engine compact while providing blistering performance.

Best-in-class power-to-weight ratio.

- 0-60 in 2.93s. Top speed of 160 km/h.

Track Tuned 6-Speed Gearbox

The racing gearbox has negative back rack gears for precision shifts and quick launches.

CRAFTED FOR AGILITY

Layout





Racing Origin Trellis Frame

- · Light weight trellis frame provides high dynamic
- stiffness.

 The forged aluminium die-cast swing arm offers greater stability.

Race Tuned KYB Suspension

- Honed and tuned by experts from KYB.
 Monoshock with Monotube floating piston technology.
 Hydraulic stopper with check valves provide better





SPECIFICATIONS

#PureRacecraft

SI, 4 stroke, 4 valve, Single cylinder, Liquid cooled, Reverse inclined

Engine Capacity

25 kW @ 9700 engine rpm (34 PS @ 9700 engine rpm) Maximum Power

Maximum Torque 27.3 Nm @ 7700 engine rpm

Bore 80 mm

Stroke 62.1 mm

Carburettor/Fuel Injection Bosch Closed loop EFI Bore to Stroke Ratio 1.29

Electric start Starting Idle speed 1700 ± 200rpm

Dynamically controlled integrated high Ignition

energy ignition system

Power to Weight Ratio 0.147 kW/kg Compression Ratio 10.9:1

Air Filter Dry Paper filter Liquid cooled Cooling System

Muffler Single pipe and single body design

Clutch Wet multi plate - 7 plate design, RT Slipper Clutch

Gear Box

Trellis frame, split chassis

Front Suspension Inverted cartridge telescopic fork Two arm aluminium die-cast swingarm

Mono tube floating piston gas assisted shock absorber

1135 mm 2001 mm Length Width 786 mm 1365 mm Wheelbase **Ground Clearance** 180 mm 810 mm Saddle Height

12V, 8Ah

Bi-LED projector, 30W @ 13 V Headlamp

LED 4 W Tail Lamp

Wheel and Tyre

Rim Size (front) MT 3.0x17 Rim Size (rear) MT 4.0x17

Tyre Size (front) 110/70-R17 M/C 54H Tubeless Tyre Size (rear) 150/60-R17 M/C 66H Tubeless

Front Disc 300mm Petal type with ABS Rear Disc 240mm Petal type with ABS Brake Fluid

160 km/h

Kerb Weight 169.5 kg Max Payload 130 kg

Max speed

Acceleration 0-2sec 46.77 km/h (speed in km/h) 0-60km/h (time in sec) 2.93 s 7.17 s 0-100km/h (time in sec)









TVS MOTOR COMPANY LIMITED. P.B. No.4, Harita, Hosur, 635109, Tamil Nadu, India. Telephone: +91 (4344) 276780. Fax: +91 (4344) 276878 / 277311 www.tvsapache.com









Crafted to be invisible. Crafted to stay invincible. The ultimate track weapon, now in Phantom Black.



