



- THE ALL NEW 2025 -

# Apache

## RTR 310

### TVS APACHE RTR 310 BS VI SPECIFICATIONS

#### Engine

|                 |  |
|-----------------|--|
| Type            | Single Cylinder, 4 Stroke, Fuel-Injected, Liquid-Cooled, Spark Ignited Reverse-Inclined Engine |
| Engine capacity | 312.12 cc  |
| Maximum Power   | Sport, Track and SuperMoto mode 35.6 PS@9700 rpm<br>Urban and Rain mode 27.1 PS @7650 rpm      |
| Maximum Torque  | Sport, Track and Supermoto mode 28.7 Nm @6650 rpm<br>Urban and Rain mode 27.3 Nm @6700 rpm     |
| Bore            | 80 mm  |
| Stroke          | 62.1 mm  |
| Cooling system  | Liquid-Cooled  |

#### Chassis and Suspension

|                  |   |
|------------------|---|
| Frame            | Hybrid with Trellis frame and Aluminium cast                                      |
| Front Suspension | USD fork 41 mm diameter   |
| Rear Suspension  | Solid Die-Cast Aluminium Swingarm directly hinged monoshocks, pre-load adjustable |

#### Electrical

|                      |                                       |
|----------------------|---------------------------------------|
| Battery              | 12V, 8AH MF Lead Acid                 |
| Headlamp             | 12V, Class-D LED Reflectors           |
| Tail Lamp            | LED 4W                                |
| Instrumental Cluster | 5" TFT GEN-2 Screen Connected Cluster |

#### Wheel and Tyre

|                   |                                       |
|-------------------|---------------------------------------|
| Tyre Size (front) | 110/70-R17 Tubeless - Michelin Road 5 |
| Tyre Size (rear)  | 150/60-R17 Michelin Road 5            |

#### Brake

|       |              |
|-------|--------------|
| Front | 300mm        |
| Rear  | 240mm        |
| ABS   | Dual-Channel |

#### Dimension

|                  |                      |
|------------------|----------------------|
| Height           | 1154 ± 10 mm         |
| Length           | 1991 ± 20 mm         |
| Width            | 831 ± 5 mm           |
| Wheelbase        | 1358 ± 12 mm         |
| Ground Clearance | 180 ± 5 mm (Unladen) |
| Saddle Height    | 800 ± 10 mm          |



FIERY RED



FURY YELLOW



ARSENAL BLACK



SEPANG BLUE

### WHAT'S NEW

- TRANSPARENT CLUTCH COVER
- AGGRESSIVE KNUCKLE GUARD
- SEQUENTIAL TURN INDICATORS (TSL)
- DRAG-TORQUE CONTROL
- KEYLESS RIDE
- LAUNCH CONTROL
- CORNERING DRAG-TORQUE CONTROL
- 5" GEN-2 TFT CLUSTER

### SEGMENT-FIRST FEATURES

- BI-DIRECTIONAL QUICKSHIFTER
- CRUISE CONTROL
- 5 RIDE MODES WITH SUPERMOTO
- CLASS-D LED REFLECTORS
- DYNAMIC TWIN TAIL LAMP

#### DYNAMIC KIT

- BRASS COATED DRIVE CHAIN
- TPMS (TYRE PRESSURE MONITORING SYSTEM)
- ADJUSTABLE FRONT FORKS (PRELOAD + DAMPING)
- ADJUSTABLE MONO SHOCK (PRELOAD + DAMPING)

#### DYNAMIC PRO KIT

- KEYLESS RIDE CONTROL
- CORNERING CRUISE CONTROL
- LAUNCH CONTROL
- REAR LIFT-OFF CONTROL
- CORNERING TRACTION CONTROL
- CORNERING DRAG-TORQUE CONTROL
- CORNERING ABS CONTROL
- WHEELIE CONTROL
- SLOPE DEPENDENT CONTROL

**TVS**  
**BUILT TO ORDER**

**TVS MOTOR COMPANY** **TVS**

TVS Motor Company Limited, P.B. No. 4, Harita, Hosur - 635 109, Tamil Nadu, India. Telephone: +91 (4344) 276878 / 277311.

#TVSApacheSeries | [www.tvs-motor.com/tvs-apache](http://www.tvs-motor.com/tvs-apache)

