SPECIFICATIONS

ENGINE

Engine Type Air-cooled, 4-stroke, SOHC, 2-valve

Displacement 149 cc

Bore & Stroke 57.3 mm \times 57.9 mm

Compression Ratio 9.6:1

Maximum Horsepower 9.1kW (12.4PS) /7250 r/min

Maximum Torque 13.3 N•m (1.4kgf•m)/

5500 r/min

Starting System Type Electric Starter Ignition TCI (Transistor

TCI (Transistor Controlled Ignition)

DIMENSIONS

Overall Length 2,020 mm
Overall Width 785 mm
Overall Height 1,115 mm
Seat Height 810 mm
Wheelbase 1,330 mm
Ground Clearance 165 mm

CHASSIS

Tyre Size (Front) 100/80-17M/C 52P Tubeless

Tyre Size (Rear) 140/60R17M/C 63P Radial Tubeless

Brake Type (Front) Disc 282 mm with ABS
Brake Type (Rear) Disc 220 mm

OTHER INFORMATION

Fuel Tank Capacity 10 I
Fuel Supply System Fuel In

Fuel Supply System

Clutch

Transmission Type

Fuel Injection

Wet, Multiple-Disc

Constant Mesh, 5-speed

Front Suspension Telescopic Fork, 41mm Inner
Tube Diameter, with Fork Boot

Rear Suspension 7-Step Adjustable Monocross Suspension

Headlight Bi-Functional LED

Brake/Tail Light LED
Auxiliary Lights LED

Clock Digital, Auto Adjust with Smart Phone Connectivity

Instrument Cluster LCD with Smart Phone Connectivity

Equipped

Battery 12 V
Traction Control System Equipped
ECO Indicator Equipped
Power Socket Equipped
Bluetooth Equipped

(Y-Connect)

Side Stand Engine Cut-Off Switch

COLOUR VARIANTS

NEVV

DARK MATTE BLU



MATTE COPPER

MATTE BLACK





Weight (with oil & a

full fuel tank)



139 kg





he specifications and designs of the motorcycles shown here may vary according to the requirements and are subject to change without prior notice. Colours shown may or match the actual colour due to printing limitations. Conditions apply. "Warranty extended for Engine, FI system, AIS system and Electricals including wiring harness, whichever is earlier. Syvear warranty" only applicable in case of purchase of Yamaha Protection Plus Policy during validity period. Please refer to Yamaha Protection Plus locations and state.

Yamaha Motor India Sales Pvt. Ltd., AKDR Tower-5th Floor, Door No. 3/381, Rajiv Gandhi Salai (OMR) Mettukuppam, Chennai - 600097. Phone: 044-3814 7000. Toll-Free No.: 1800 420 1600 Email: info@yamaha-motor-india.com www.yamaha-motor-india.com

Authorised Dealer





TRACTION CONTROL 5 Y 5 T E M

- > Reduces rear tyre slippage
- **▶** Better control in any riding condition

149cc Fi

Trusted & Efficient 149cc Fi Engine



The FZ-X comes with the trusted & efficient air-cooled, 4-stroke, 149cc SOHC, 2-valve, single-cylinder fuel-injected engine that is in a league of its own.







LCD METER

The sleek and stylish LCD instrument screen is a mix of both, traditional and modern design. The tachometer display in it has an analogue look that shows the revs in a circular pattern. This display also shows smartphone notifications accurately and attractively.





The power socket provides a convenient charging slot for mobile phones and other personal devices.



FEATURES



LED FLASHERS



SLEEK LED TAIL LIGHT



BI-FUNCTIONAL LED HEADLIGHT WITH DRL





TWO-LEVEL SEAT WITH TUCK AND ROLL



BLOCK PATTERN TYRES



TELESCOPIC SUSPENSION WITH FRONT FORK BOOTS

MOBILE PHONE NOTIFICATIONS













METER CONSOLE NOTIFICATIONS







SMS & EMAIL ALERT



PHONE BATTERY LEVEL